NSN 5340-01-154-3152

Spacing Threaded Standoff - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5340-01-154-3152 |
|---|
| Thread Class: |
| 2b left internal (includes through thread)2a right external |
| Thread Direction: |
| Right-hand right external |
| Thread Length: |
| 0.250 inches left internal (includes through thread)0.188 inches right external |
| Flange Thickness: |
| Between 1.526 inches and 1.536 inches |
| Length: |
| Between 1.714 inches and 1.724 inches |
| Flange Width Across Flats: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 40 right external |
| Thread Size: |
| 0.112 inches left internal (includes through thread) |
| Material: |
| Aluminum alloy 2011 standoff |
| Material Specification: |
| Qq-a-225/3b t3 federal specification single material response standoff |
| Surface Treatment: |
| Chromium standoff |
| Surface Treatment Specification: |
| Mil-c-5541 military specification single treatment response standoff |
| Style Designator: |
| Flanged with left internal thread |
| Thread Series Designator: |
| Unc right external |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A08000 |

Mil-std (military Standard):

Mil-c-5541 spec.