

View Online at <https://aerobasegroup.com/nsn/5340-01-155-8126>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.375 inches

**Second Leg Length:**

0.422 inches

**End Application:**

Ks87b

**Second Leg Width:**

1.250 inches

**First Leg Slot Length:**

0.250 inches

**First Leg Slot Width:**

0.125 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.125 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.188 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.188 inches

**Second Leg Slot Length:**

0.250 inches

**Second Leg Slot Width:**

0.125 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

1.250 inches

**First Leg Distance Between Hole Centers Along Width:**

1.125 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.188 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.125 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

2nd leg has cut out 0.750 in. L, 0.094 in. Deep approximately 0.375 in. From end along leg lgth 2 places and 1st leg is chamfered 0.062 in.

By 45 deg. 2 places; surface treatment: alodine

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250 federal specification single material response

**Surface Treatment Specification:**

Cad-127 mfr ref single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0