

View Online at <https://aerobasegroup.com/nsn/5340-01-155-8126>

Mounting Hole Type:

Plain

First Leg Length:

0.375 inches

Second Leg Length:

0.422 inches

End Application:

Ks87b

Second Leg Width:

1.250 inches

First Leg Slot Length:

0.250 inches

First Leg Slot Width:

0.125 inches

Second Leg Distance Between Hole Centers Along Width:

1.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.188 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.188 inches

Second Leg Slot Length:

0.250 inches

Second Leg Slot Width:

0.125 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

1.250 inches

First Leg Distance Between Hole Centers Along Width:

1.125 inches

First Leg Distance From Edge To Hole Center Along Width:

0.188 inches

First Leg Distance From Edge To Hole Center Along Length:

0.125 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

2nd leg has cut out 0.750 in. L, 0.094 in. Deep approximately 0.375 in. From end along leg lgth 2 places and 1st leg is chamfered 0.062 in.

By 45 deg. 2 places; surface treatment: alodine

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250 federal specification single material response

Surface Treatment Specification:

Cad-127 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0