

View Online at <https://aerobasegroup.com/nsn/5340-01-157-2497>

**First Leg Length:**

1.120 inches

**Second Leg Length:**

2.750 inches

**End Application:**

USEO-NG-ENE-RATO

**Second Leg Width:**

4.380 inches

**First Leg Slot Length:**

0.614 inches

**First Leg Slot Width:**

0.307 inches

**Second Leg Hole Diameter:**

0.370 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.812 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

4.000 inches

**First Leg Thickness:**

0.119 inches

**Second Leg Thickness:**

0.119 inches

**First Leg Width:**

2.500 inches

**First Leg Distance Between Hole Centers Along Length:**

1.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

Mil-t-704, type f military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-t-704 spec.