

View Online at <https://aerobasegroup.com/nsn/5340-01-157-4816>

Mounting Hole Type:

Counterbored

First Leg Length:

0.700 inches

Second Leg Length:

0.700 inches

Second Leg Width:

3.861 inches

Second Leg Corner Radius:

0.310 inches

First Leg Hole Diameter:

Between 0.280 inches and 0.285 inches

Second Leg Distance Between Hole Centers Along Width:

3.241 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.310 inches

Second Leg Slot Length:

0.290 inches

Second Leg Slot Width:

0.215 inches

First Leg Thickness:

0.100 inches

Second Leg Thickness:

0.100 inches

Center Section Height:

1.835 inches

Center Section Width:

3.700 inches

Center Section Thickness:

0.100 inches

First Leg Width:

3.230 inches

First Leg Corner Radius:

0.240 inches

First Leg Distance Between Hole Centers Along Width:

2.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.240 inches

First Leg Distance From Edge To Hole Center Along Length:

0.240 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

Second Leg Angle:

6.0 degrees

First Leg Offset Angle:

6.0 degrees

Special Features:

First leg holes counterbored, 0.375 in. Min and 0.395 in. Maximum dia, 0.035 in. Min and 0.045 in. Maximum dp; two nuts also provided

Material:

Titanium alloy

Material Specification:

Ams4902 assn standard single material response

Style Designator:

Offset double angle

Fsc Application Data:

Engine model f404

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0