

View Online at <https://aerobasegroup.com/nsn/5340-01-160-2158>

Mounting Hole Type:

Plain

First Leg Length:

0.940 inches

Second Leg Length:

2.250 inches

Second Leg Width:

5.000 inches

Second Leg End Width:

4.850 inches

First Leg Hole Diameter:

Between 0.220 inches and 0.230 inches

Second Leg Hole Diameter:

Between 1.220 inches and 1.230 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

1.406 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

1.406 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.090 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

5.000 inches

First Leg Distance Between Hole Centers Along Width:

4.375 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.378 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

6 threaded holes on second leg 6-32unc-2b and 2 additional mounting holes 0.220 in. Dia

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, th32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.