

View Online at <https://aerobasegroup.com/nsn/5340-01-160-4591>

Mounting Hole Type:

Plain

First Leg Length:

2.750 inches

Second Leg Length:

4.240 inches

Reinforcement Method (non-core):

Gusset center section

First Leg Hole Diameter:

Between 0.391 inches and 0.406 inches

Second Leg Hole Diameter:

Between 1.005 inches and 1.010 inches

Second Leg Distance Between Hole Centers Along Length:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.800 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.800 inches

First Leg Thickness:

Between 0.139 inches and 0.155 inches

Second Leg Thickness:

Between 0.139 inches and 0.155 inches

First Leg Width:

3.180 inches

First Leg Distance Between Upper Hole Centers Along Width:

1.000 inches

First Leg Distance Between Hole Centers Along Length:

1.340 inches

First Leg Distance From Edge To Hole Center Along Width:

0.910 inches

First Leg Distance From Edge To Hole Center Along Length:

0.280 inches

Second Leg End Radius:

0.800 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Second hole on second leg 0.551 min and 0.559 maximum diameter

Material:

Steel comp 1008 or steel comp 1010

Material Specification:

Sae assn standard all material responses

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0