NSN 5340-01-160-4592

Angle Bracket - Page 1 of 2

Mounting Hole Type:

First Leg Length:

Plain



View Online at https://aerobasegroup.com/nsn/5340-01-160-4592

| 2.460 inches |
|--|
| Second Leg Length: |
| 2.900 inches |
| Second Leg Width: |
| 7.620 inches |
| Second Leg Hole Diameter: |
| Between 0.281 inches and 0.285 inches |
| Second Leg Distance Between First And Second Hole Centers Along Width: |
| 1.500 inches |
| Second Leg Distance Between Second And Third Hole Centers Along Width: |
| 4.560 inches |
| Second Leg Distance From Edge To Hole Center Along Width: |
| 0.780 inches |
| First Leg Thickness: |
| Between 0.038 inches and 0.062 inches |
| Second Leg Thickness: |
| Between 0.038 inches and 0.062 inches |
| First Leg Width: |
| 7.620 inches |
| First Leg Distance Between First And Second Hole Centers Along Width: |
| 1.440 inches |
| First Leg Distance Between Second And Third Hole Centers Along Width: |
| 1.440 inches |
| First Leg Distance From Edge To Hole Center Along Width: |
| 0.370 inches |
| First Leg Distance From Edge To Hole Center Along Length: |
| 1.180 inches |
| First Leg Style: |
| Square |
| Second Leg Style: |
| Square |
| Second Leg Hole Arrangement Style: |
| Three holes |
| Features Provided: |
| Nut |
| Second Leg Relationship To First Leg: |
| Not identical |
| Special Features: |
| First leg has four holes 0.250 in. Min 0.254 in. Maximum also one hole 0.196 in. Min 0.212 in. Max; other hole 0.125 in. Min 0.134 in. Max |

NSN 5340-01-160-4592 Angle Bracket - Page 2 of 2

Fiig: A042a0



| Material: |
|--|
| Steel comp 1008 or steel comp 1010 |
| Material Specification: |
| Sae assn standard single material response |
| Surface Treatment: |
| Cadmium and zinc |
| Surface Treatment Specification: |
| Gm 4342-m fscm 11862 mfr ref all treatment responses |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |