

View Online at <https://aerobasegroup.com/nsn/5340-01-161-2637>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.620 inches

**Second Leg Length:**

0.620 inches

**Reinforcement Method (non-core):**

Rib stiffener both legs

**Second Leg Width:**

1.000 inches

**Second Leg Corner Radius:**

0.031 inches

**Second Leg Hole Diameter:**

Between 0.169 inches and 0.174 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.310 inches

**First Leg Thickness:**

Between 0.027 inches and 0.037 inches

**Second Leg Thickness:**

Between 0.027 inches and 0.037 inches

**Center Section Height:**

0.500 inches

**Center Section Width:**

1.000 inches

**Center Section Thickness:**

Between 0.027 inches and 0.037 inches

**First Leg Width:**

1.000 inches

**First Leg Corner Radius:**

0.310 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

No hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

One hole

**Features Provided:**

Nut

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5 federal specification single material response

**Surface Treatment:**

Plastic epoxy

**Surface Treatment Specification:**

Mil-p-23377 military specification single treatment response

**Style Designator:**

Double angle

**Specification Data:**

26512-gb23j1a08 manufacturers specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-p-23377 spec.