

View Online at <https://aerobasegroup.com/nsn/5340-01-161-4734>

First Leg Length:

0.700 inches

Second Leg Length:

0.875 inches

Second Leg Width:

3.550 inches

Second Leg End Width:

3.460 inches

First Leg Slot Length:

Between 0.302 inches and 0.322 inches

First Leg Slot Width:

Between 0.177 inches and 0.197 inches

Second Leg Distance Between Hole Centers Along Width:

2.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.400 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.332 inches

Second Leg Slot Length:

Between 0.302 inches and 0.322 inches

Second Leg Slot Width:

Between 0.177 inches and 0.197 inches

First Leg Thickness:

0.094 inches

Second Leg Thickness:

0.094 inches

First Leg Width:

3.550 inches

First Leg End Width:

3.300 inches

First Leg Distance Between Hole Centers Along Width:

1.110 inches

First Leg Distance From Edge To Hole Center Along Length:

0.350 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

3 holes in 1st leg 0.165 in. Diameter min, 0.171 in. Diameter max

Material:

Aluminum alloy 6061 or aluminum alloy 6063

Material Specification:

Qq-a-225/8, alloy 6061, t4 or t6 federal specification single material response or qq-a200/9, alloy 6063, t5 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.