

View Online at <https://aerobasegroup.com/nsn/5340-01-161-4734>

**First Leg Length:**

0.700 inches

**Second Leg Length:**

0.875 inches

**Second Leg Width:**

3.550 inches

**Second Leg End Width:**

3.460 inches

**First Leg Slot Length:**

Between 0.302 inches and 0.322 inches

**First Leg Slot Width:**

Between 0.177 inches and 0.197 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.750 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.400 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.332 inches

**Second Leg Slot Length:**

Between 0.302 inches and 0.322 inches

**Second Leg Slot Width:**

Between 0.177 inches and 0.197 inches

**First Leg Thickness:**

0.094 inches

**Second Leg Thickness:**

0.094 inches

**First Leg Width:**

3.550 inches

**First Leg End Width:**

3.300 inches

**First Leg Distance Between Hole Centers Along Width:**

1.110 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.350 inches

**First Leg Style:**

Square and tapered

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Square and tapered

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

3 holes in 1st leg 0.165 in. Diameter min, 0.171 in. Diameter max

**Material:**

Aluminum alloy 6061 or aluminum alloy 6063

**Material Specification:**

Qq-a-225/8, alloy 6061, t4 or t6 federal specification single material response or qq-a200/9, alloy 6063, t5 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.