

View Online at <https://aerobasegroup.com/nsn/5340-01-161-5523>

Mounting Hole Type:

Plain

First Leg Length:

1.050 inches

Second Leg Length:

10.000 inches

Reinforcement Method (non-core):

Err-070

End Application:

2320-01-304-2277 and 2320-01-304-2278 pls (palletized loading system)

Second Leg Width:

6.500 inches

First Leg Slot Length:

0.560 inches

First Leg Slot Width:

0.280 inches

Second Leg Hole Diameter:

0.280 inches

Second Leg Distance Between Hole Centers Along Width:

6.000 inches

Second Leg Distance Between Hole Centers Along Length:

3.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

3.120 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.500 inches

First Leg Thickness:

0.0747 inches

Second Leg Thickness:

0.0747 inches

First Leg Width:

6.000 inches

First Leg Distance Between Hole Centers Along Width:

4.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Gusset has 3 slots

Material:

Steel comp 1020

Material Specification:

Sae assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0