## NSN 5340-01-162-3100

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-162-3100

1.942 inches         End Application:         11133 pw102 engine, kc-135         First Leg Hole Diameter:         Between 0.214 inches and 0.224 inches         Second Leg Diatance Between Hole Centers Along Width:         0.036 inches         Second Leg Diatance Between Hole Centers Along Width:         0.036 inches         Second Leg Diatance Between Hole Centers Along Width:         0.036 inches         Second Leg Diatance From Edge To Hole Center Along Width:         0.312 inches         Second Leg Diatance From Edge To Hole Center Along Length:         0.312 inches         Second Leg Diatance From Edge To Hole Center Along Length:         0.312 inches         Second Leg Diatance From Edge To Hole Center Along Length:         0.312 inches         Between 0.064 inches and 0.076 inches         Second Leg End Radius:         0.250 inches         Second Leg End Radius:         0.312 inches         First Leg End Radius:         0.325 inches         Second Leg Hole Arrangement Style:         Totalius and tapered         Second Leg Relationship To First Leg:         Not identica         First Leg Angle:         0.00 degrees         Secoid Leg Relationship To First Leg<	Second Log Longth.
End Application:         T1133 pw102 engine, kc-135         First Leg Hole Diameter:         Between 0.214 inches and 0.224 inches         Second Leg Diameter:         Between 0.276 inches and 0.286 inches         Second Leg Distance Between Hole Centers Along Width:         0.036 inches         Second Leg Distance Between Hole Centers Along Length:         1.030 inches         Second Leg Distance From Edge To Hole Center Along Width:         0.312 inches         Second Leg Distance From Edge To Hole Center Along Length:         0.312 inches         Second Leg Distance From Edge To Hole Center Along Length:         0.312 inches         Second Leg Distance From Edge To Hole Center Along Length:         0.312 inches         First Leg Thickness:         Between 0.064 inches and 0.076 inches         Second Leg End Radius:         0.250 inches         Second Leg End Radius:         0.312 inches         First Leg Style:         End angle Leg Angle         0.321 inches         Second Leg Relationship To First Leg:         Not identical         First Leg Angle:         0.30 degrees         Second Leg Relationship To First Leg:         Not identical	Second Leg Length:
Trist Leg Hole Diameter:         Between 0.214 inches and 0.224 inches         Second Leg Hole Diameter:         Between 0.276 inches and 0.286 inches         Second Leg Distance Between Hole Centers Along Width:         0.036 inches         Second Leg Distance Between Hole Centers Along Width:         0.030 inches         Second Leg Distance From Edge To Hole Center Along Width:         0.312 inches         Second Leg Distance From Edge To Hole Center Along Length:         0.312 inches         Between 0.064 inches and 0.076 inches         Second Leg Thickness:         Between 0.064 inches and 0.076 inches         Second Leg End Radius:         0.312 inches         Between 0.064 inches and 0.076 inches         First Leg End Radius:         0.350 inches         Second Leg Distance From Edge To Hole Center Along Length:         0.320 inches         Between 0.064 inches and 0.076 inches         First Leg End Radius:         0.350 inches         Second Leg Ede Radius:         0.312 inches         First Leg Style:         End radius and tapered         Second Leg Belationship To First Leg:         Not identical         First Leg Angle:         0.0 degrees	
First Leg Hole Diameter:         Between 0.214 inches and 0.224 inches         Second Leg Hole Diameter:         Between 0.276 inches and 0.286 inches         Second Leg Distance Between Hole Centers Along Width:         0.036 inches         Second Leg Distance Between Hole Centers Along Length:         1.030 inches         Second Leg Distance From Edge To Hole Center Along Width:         0.312 inches         Second Leg Distance From Edge To Hole Center Along Length:         0.312 inches         Between 0.064 inches and 0.076 inches         Second Leg Thickness:         Between 0.064 inches and 0.076 inches         Second Leg Thickness:         Between 0.064 inches and 0.076 inches         Second Leg Thickness:         Between 0.064 inches and 0.076 inches         First Leg End Radius:         0.312 inches         First Leg Style:         Between 0.064 inches and 0.076 inches         Second Leg Beta Radius:         0.312 inches         First Leg Style:         Between 0.064 inches and 0.076 inches         Second Leg Beta Radius:         0.312 inches         First Leg Style:         Between 0.064 inches         Second Leg Style Det Arrangement Style:         Not ide	
Between 0.214 inches and 0.224 inches         Second Leg Hole Diameter:         Between 0.276 inches and 0.286 inches         Second Leg Distance Between Hole Centers Along Width:         0.036 inches         Second Leg Distance Between Hole Centers Along Length:         1.030 inches         Second Leg Distance From Edge To Hole Center Along Width:         0.312 inches         Second Leg Distance From Edge To Hole Center Along Length:         0.312 inches         Second Leg Distance From Edge To Hole Center Along Length:         0.312 inches         Second Leg Thickness:         Between 0.064 inches and 0.076 inches         Second Leg Thickness:         Between 0.064 inches and 0.076 inches         Second Leg End Radius:         0.250 inches         Second Leg End Radius:         0.312 inches         First Leg Style:         End radius and tapered         Second Leg Relationship To First Leg:         Not identical         First Leg Angle:         0.00 degrees         Special Features:         1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in.         Material Specification:         Atorial Specification:         Material Specification:	
Second Leg Hole Diameter: Between 0.276 inches and 0.286 inches Second Leg Distance Between Hole Centers Along Width: 0.036 inches Second Leg Distance Between Hole Centers Along Length: 1.030 inches Second Leg Distance From Edge To Hole Center Along Width: 0.312 inches Second Leg Distance From Edge To Hole Center Along Width: 0.312 inches Second Leg Distance From Edge To Hole Center Along Length: 0.312 inches First Leg Thickness: Between 0.064 inches and 0.076 inches Second Leg End kadius: 0.250 inches Second Leg End Radius: 0.312 inches First Leg End Radius: 0.312 inches First Leg Style: End radius and tapered Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 0.00 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Ams 5504 asan standard single material response	-
Between Joe         Second Leg Distance Between Hole Centers Along Width:         0.036 inches         Second Leg Distance Between Hole Centers Along Length:         1.030 inches         Second Leg Distance From Edge To Hole Center Along Width:         0.312 inches         Second Leg Distance From Edge To Hole Center Along Width:         0.312 inches         Second Leg Distance From Edge To Hole Center Along Length:         0.312 inches         Between 0.064 inches and 0.076 inches         Second Leg Thickness:         Between 0.064 inches and 0.076 inches         First Leg End Radius:         0.250 inches         Second Leg End Radius:         0.312 inches         Second Leg End Radius:         0.312 inches         First Leg Style:         End radius and tapered         Second Leg Relationship To First Leg:         Not identical         First Leg Angle:         9.00 degrees         Special Features:         1st Leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in.         Material Specification:         Anst 5504 asan standard single material response         Style Designator:	
Second Leg Distance Between Hole Centers Along Width:0.036 inchesSecond Leg Distance Between Hole Centers Along Length:1.030 inchesSecond Leg Distance From Edge To Hole Center Along Width:0.312 inchesBetome Leg Distance From Edge To Hole Center Along Length:0.312 inchesSecond Leg Distance From Edge To Hole Center Along Length:0.312 inchesBetween 0.064 inches and 0.076 inchesSecond Leg Thickness:Between 0.064 inches and 0.076 inchesSecond Leg Thickness:Between 0.064 inches and 0.076 inchesSecond Leg End Radius:0.320 inchesSecond Leg End Radius:0.312 inchesSecond Leg End Radius:0.312 inchesSecond Leg End Radius:0.312 inchesSecond Leg Role Arrangement Style:Catol Leg Alole Arrangement Style:Not identicalFirst Leg Angle:9.0.0 degreesSpecial Features:1.12 Stell Head Alor 0.70 in. Diameter with 3 holes en pan al located on a diameter of 1.250 in.Material Specification:Aterial Specification:Aterial Specification:Aterial Specification:Atter Stold assn standard single material responseStyle Designator:	-
0.036 inchesSecond Leg Distance Between Hole Centers Along Length:1.030 inchesSecond Leg Distance From Edge To Hole Center Along Width:0.312 inchesSecond Leg Distance From Edge To Hole Center Along Length:0.312 inchesFirst Leg Thickness:Between 0.064 inches and 0.076 inchesSecond Leg Thickness:Between 0.064 inches and 0.076 inchesSecond Leg Thickness:Between 0.064 inches and 0.076 inchesSecond Leg End Radius:0.250 inchesSecond Leg End Radius:0.312 inchesSecond Leg End Radius:0.312 inchesSecond Leg Relationship To First Leg:Not identicalFirst Leg Angle:0.00 degreesSecond Leg Relationship To First Leg:Not identicalFirst Leg Angle:0.00 degreesSecond Leg Relationship To First Leg:Not identicalFirst Leg Angle:0.00 degreesSpecial Features:1 st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in.Material Specification:Austerial Specification:Auster	
Second Leg Distance Between Hole Centers Along Length: 1.030 inches Second Leg Distance From Edge To Hole Center Along Width: 0.312 inches Second Leg Distance From Edge To Hole Center Along Length: 0.312 inches First Leg Thickness: Between 0.064 inches and 0.076 inches Second Leg Thickness: Between 0.064 inches and 0.076 inches Second Leg End Radius: 0.250 inches Second Leg End Radius: 0.312 inches Second Leg End Radius: 0.312 inches First Leg Style: End radius and tapered Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 9.00 degrees Special Features: 1 st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material Stele Material Specification: Atterial Specification: Atterial Specification: Atterial Specification: Atter St04 assn standard single material response Style Designator:	
1.030 inches         Second Leg Distance From Edge To Hole Center Along Width:         0.312 inches         Second Leg Distance From Edge To Hole Center Along Length:         0.312 inches         First Leg Thickness:         Between 0.064 inches and 0.076 inches         Second Leg Thickness:         Between 0.064 inches and 0.076 inches         Second Leg Thickness:         Between 0.064 inches and 0.076 inches         First Leg End Radius:         0.250 inches         Second Leg End Radius:         0.312 inches         First Leg Style:         End radius and tapered         Second Leg Relationship To First Leg:         Not identical         First Leg Angle:         90.0 degrees         Special Features:         1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in.         Material         Steel         Material Specification:         Ans 5504 assn standard single material response         Style Designator:	
Second Leg Distance From Edge To Hole Center Along Width: 0.312 inches Second Leg Distance From Edge To Hole Center Along Length: 0.312 inches First Leg Thickness: Between 0.064 inches and 0.076 inches Second Leg Thickness: Between 0.064 inches and 0.076 inches First Leg End Radius: 0.250 inches Second Leg End Radius: 0.312 inches First Leg Style: End radius and tapered Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Stel Material Specification: Ams 5504 assn standard single material response Style Designator:	
0.312 inches         Second Leg Distance From Edge To Hole Center Along Length:         0.312 inches         First Leg Thickness:         Between 0.064 inches and 0.076 inches         Second Leg Thickness:         Between 0.064 inches and 0.076 inches         First Leg End Radius:         0.250 inches         Second Leg End Radius:         0.250 inches         Second Leg End Radius:         0.312 inches         First Leg Style:         End radius and tapered         Second Leg Relationship To First Leg:         Not identical         First Leg Angle:         90.0 degrees         Special Features:         1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in.         Material         Steel         Material Specification:         Arst 5504 assn standard single material response         Style Designator:	1.030 inches
Second Leg Distance From Edge To Hole Center Along Length: 0.312 inches First Leg Thickness: Between 0.064 inches and 0.076 inches Second Leg Thickness: Between 0.064 inches and 0.076 inches First Leg End Radius: 0.250 inches Second Leg End Radius: 0.250 inches Second Leg End Radius: 0.312 inches First Leg Style: End radius and tapered Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Arms 5504 assn standard single material response Style Designator:	Second Leg Distance From Edge To Hole Center Along Width:
0.312 inchesFirst Leg Thickness:Between 0.064 inches and 0.076 inchesSecond Leg Thickness:Between 0.064 inches and 0.076 inchesFirst Leg End Radius:0.250 inchesSecond Leg End Radius:0.312 inchesSecond Leg End Radius:0.312 inchesFirst Leg Style:End radius and taperedSecond Leg Hole Arrangement Style:Two holesSecond Leg Relationship To First Leg:Not identicalFirst Leg Angle:90.0 degreesSpecial Features:1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in.Material Specification:Ams 5504 assn standard single material responseStyle Designator:	0.312 inches
First Leg Thickness:         Between 0.064 inches and 0.076 inches         Second Leg Thickness:         Between 0.064 inches and 0.076 inches         First Leg End Radius:         0.250 inches         Second Leg End Radius:         0.312 inches         First Leg Style:         Bet dation and tapered         Second Leg Hole Arrangement Style:         Two holes         Second Leg Relationship To First Leg:         Not identical         First Leg Angle:         9.0.0 degrees         Secolal Features:         1st leg hashole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in         Material Specification:         Aterial Specification:         Atterial Specification:         Atterial Specification:         Atterial Specification:         Atterial Specification:	Second Leg Distance From Edge To Hole Center Along Length:
Between 0.064 inches and 0.076 inches         Second Leg Thickness:         Between 0.064 inches and 0.076 inches         First Leg End Radius:         0.250 inches         Second Leg End Radius:         0.312 inches         First Leg Style:         End radius and tapered         Second Leg Hole Arrangement Style:         Two holes         Second Leg Relationship To First Leg:         Not identical         First Leg Angle:         90.0 degrees         Special Features:         1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in.         Material         Steel         Material Specification:         Ans 5504 assn standard single material response         Style Designator:	0.312 inches
Second Leg Thickness: Between 0.064 inches and 0.076 inches First Leg End Radius: 0.250 inches Second Leg End Radius: 0.312 inches First Leg Style: End radius and tapered Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Ans 5504 assn standard single material response Style Designator:	First Leg Thickness:
Between 0.064 inches and 0.076 inches         First Leg End Radius:         0.250 inches         Second Leg End Radius:         0.312 inches         First Leg Style:         End radius and tapered         Second Leg Hole Arrangement Style:         Two holes         Second Leg Relationship To First Leg:         Not identical         First Leg Angle:         90.0 degrees         Special Features:         1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in.         Material:         Steel         Material:         Steel         Material Specification:         Ams 5504 assn standard single material response         Style Designator:	Between 0.064 inches and 0.076 inches
First Leg End Radius:         0.250 inches         Second Leg End Radius:         0.312 inches         First Leg Style:         End radius and tapered         Second Leg Hole Arrangement Style:         Two holes         Second Leg Relationship To First Leg:         Not identical         First Leg Angle:         90.0 degrees         Special Features:         1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in.         Material:         Steel         Material Specification:         Ams 5504 assn standard single material response         Style Designator:	Second Leg Thickness:
0.250 inches Second Leg End Radius: 0.312 inches First Leg Style: End radius and tapered Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Ams 5504 assn standard single material response	Between 0.064 inches and 0.076 inches
Second Leg End Radius: 0.312 inches First Leg Style: End radius and tapered Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Ams 5504 assn standard single material response Style Designator:	First Leg End Radius:
0.312 inches First Leg Style: End radius and tapered Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Ams 5504 assn standard single material response Style Designator:	0.250 inches
First Leg Style: End radius and tapered Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Ams 5504 assn standard single material response Style Designator:	Second Leg End Radius:
End radius and tapered Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Steel Material Specification: Ams 5504 assn standard single material response Style Designator:	0.312 inches
Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Ams 5504 assn standard single material response Style Designator:	First Leg Style:
Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Ams 5504 assn standard single material response Style Designator:	End radius and tapered
Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Ams 5504 assn standard single material response Style Designator:	Second Leg Hole Arrangement Style:
Not identical First Leg Angle: 90.0 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Ams 5504 assn standard single material response Style Designator:	Two holes
First Leg Angle: 90.0 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Ams 5504 assn standard single material response Style Designator:	Second Leg Relationship To First Leg:
90.0 degrees Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Ams 5504 assn standard single material response Style Designator:	Not identical
Special Features: 1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Ams 5504 assn standard single material response Style Designator:	First Leg Angle:
1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in. Material: Steel Material Specification: Ams 5504 assn standard single material response Style Designator:	90.0 degrees
Material:         Steel         Material Specification:         Ams 5504 assn standard single material response         Style Designator:	Special Features:
Steel Material Specification: Ams 5504 assn standard single material response Style Designator:	1st leg has hole 0.710-0.730 in. Diameter with 3 holes eq sp and located on a diameter of 1.250 in.
Material Specification: Ams 5504 assn standard single material response Style Designator:	Material:
Ams 5504 assn standard single material response Style Designator:	Steel
Style Designator:	Material Specification:
	Ams 5504 assn standard single material response
Angle	Style Designator:
Angle	Angle
Shelf Life:	Shelf Life:
N1/-	N/a
N/a	

## NSN 5340-01-162-3100

Angle Bracket - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A042a0

