NSN 5340-01-162-6078

Webbing Strap - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-162-6078

| Width: |
|---|
| 1.000 inches |
| Length: |
| Between 5.750 inches and 6.250 inches |
| Environmental Protection: |
| Heat resistant and light resistant |
| End Type: |
| Folded and w/attachment |
| Attachment Method For Which Designed: |
| Sewed |
| Buckle Material: |
| Steel, qq-s-698, comp 1008 through 1020, temper no.2 |
| Buckle Surface Treatment: |
| Enamel |
| Buckle Location: |
| One end |
| Fastened Buckle Feature: |
| Included |
| Buckle Fastening Method: |
| Sewed |
| Fold Type: |
| Loose |
| End Attachment/fastening Facility: |
| Buckle |
| Buckle Style Designator: |
| Spring activated |
| Material: |
| Nylon, mil-w-4088, type 25 |
| Material: |
| Plastic polyhexamethylene adipamide |
| Material Specification: |
| Mil-w-4088, type 25 military specification single material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| Т372-b |
| Mil-std (military Standard): |
| Mil-w-4088 spec. |