

View Online at <https://aerobasegroup.com/nsn/5340-01-163-1524>

**Cross Sectional Shape:**

Circular recess

**Inside Diameter:**

Between 0.251 inches and 0.253 inches

**Hole Diameter:**

Between 0.216 inches and 0.236 inches

**Flange Thickness:**

Between 0.225 inches and 0.235 inches

**Edge Shape:**

Round, two ears and holes

**Body Radius:**

0.620 inches

**Distance Between Holes Along Length:**

1.538 inches

**First Recess Inside Height:**

Between 0.480 inches and 0.580 inches

**Securing Device Type:**

Special

**Mounting Opening Shape Style:**

Unthreaded hole

**End Application:**

Main fuel pump, f100-pw-200 aircraft engine

**Special Features:**

Neck: 0.390 in. Thk, 1.057 - 1.060 in. Dia, pin hole through 0.0938 in. Maximum dia, packing groove 0.900 in. Dia; part of bypass valve, strainer assembly 105613

**Material:**

Aluminum alloy

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Ams2470 assn standard single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531c0