Angle Bracket - Page 1 of 2





Mounting Hole Type:

- Plain
- First Leg Length:
- 1.500 inches
- Second Leg Length:
- 9.000 inches
- Second Leg Width:
- 8.750 inches
- Second Leg Corner Radius:
- 0.250 inches
- First Leg Hole Diameter:
- 0.406 inches
- Second Leg Hole Diameter:
- 0.281 inches
- Second Leg Distance Between Hole Centers Along Width:
- 3.750 inches
- Second Leg Distance Between Hole Centers Along Length:
- 4.250 inches
- Second Leg Distance From Edge To Hole Center Along Length:
- 1.500 inches
- First Leg Thickness:
- 0.190 inches
- Second Leg Thickness:
- 0.190 inches
- First Leg Width:
- 5.000 inches
- First Leg Distance Between Hole Centers Along Width:
- 3.500 inches
- First Leg Distance From Edge To Hole Center Along Width:
- 0.750 inches
- First Leg Distance From Edge To Hole Center Along Length:
- 0.620 inches
- First Leg Style:
- Square
- First Leg Hole Arrangement Style:
- Two holes
- Second Leg Style:
- Corner radius
- Second Leg Hole Arrangement Style:
- Four holes
- Second Leg Relationship To First Leg:
- Not identical

NSN 5340-01-163-6528

Angle Bracket - Page 2 of 2



First Leg Angle:

90.0 degrees

Special Features:

Second leg has two holes with diameter 0.281 in., two holes with diameter 0.406 in., one hole diameter 1.000 in., left handed Material:

Steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020

Surface Treatment:

Enamel

Surface Treatment Specification:

Tt-e-529 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0