

View Online at <https://aerobasegroup.com/nsn/5340-01-168-1849>

Mounting Hole Type:

Plain

First Leg Length:

0.750 inches

Second Leg Length:

1.620 inches

Second Leg Width:

1.440 inches

Second Leg Corner Radius:

0.440 inches

First Leg Hole Diameter:

0.219 inches

Second Leg Hole Diameter:

0.531 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.440 inches

First Leg Thickness:

0.119 inches

Second Leg Thickness:

0.119 inches

Center Section Height:

2.120 inches

Center Section Width:

1.620 inches

Center Section Thickness:

0.119 inches

First Leg Width:

1.620 inches

First Leg Distance Between Hole Centers Along Width:

1.063 inches

First Leg Distance From Edge To Hole Center Along Width:

0.280 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-52798 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-e-52798 spec.