NSN 5340-01-171-4947

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-171-4947

Cross Sectional Shape:					
Square or rectangular recess					
Hole Diameter:					
0.438 inches					
Width:					
13.000 inches					
Flange Thickness:					
1.000 inches					
Edge Shape:					
Rectangle, rounded corners, four ears and holes					
Length:					
12.062 inches					
Inside Width:					
Between 8.500 inches and 11.250 inches					
Inside Length:					
Between 8.500 inches and 9.750 inches					
Corner Radius:					
0.500 inches					
Distance Between Holes Along Length:					
7.500 inches					
Distance Between Holes Along Width:					
11.500 inches					
Distance From First Hole Centerline To End Along Length:					
Distance i form i not riole contenine to Lina / nong Longian					
2.000 inches					
2.000 inches					
2.000 inches Distance From First Hole Centerline To End Along Width:					
2.000 inches Distance From First Hole Centerline To End Along Width: 0.562 inches					
2.000 inches Distance From First Hole Centerline To End Along Width: 0.562 inches Inverted Radius:					
2.000 inches Distance From First Hole Centerline To End Along Width: 0.562 inches Inverted Radius: 0.500 inches					
2.000 inches Distance From First Hole Centerline To End Along Width: 0.562 inches Inverted Radius: 0.500 inches Ear Radius:					
2.000 inches Distance From First Hole Centerline To End Along Width: 0.562 inches Inverted Radius: 0.500 inches Ear Radius: 0.625 inches					
2.000 inches Distance From First Hole Centerline To End Along Width: 0.562 inches Inverted Radius: 0.500 inches Ear Radius: 0.625 inches First Recess Inside Height:					
2.000 inches Distance From First Hole Centerline To End Along Width: 0.562 inches Inverted Radius: 0.500 inches Ear Radius: 0.625 inches First Recess Inside Height: 8.500 inches					
2.000 inches Distance From First Hole Centerline To End Along Width: 0.562 inches Inverted Radius: 0.500 inches Ear Radius: 0.625 inches First Recess Inside Height: 8.500 inches Inside Corner Radius: 4.000 inches					
2.000 inches Distance From First Hole Centerline To End Along Width: 0.562 inches Inverted Radius: 0.500 inches Ear Radius: 0.625 inches First Recess Inside Height: 8.500 inches Inside Corner Radius:					
2.000 inches Distance From First Hole Centerline To End Along Width: 0.562 inches Inverted Radius: 0.500 inches Ear Radius: 0.625 inches First Recess Inside Height: 8.500 inches Inside Corner Radius: 4.000 inches Body Thickness:					
2.000 inches Distance From First Hole Centerline To End Along Width: 0.562 inches Inverted Radius: 0.500 inches Ear Radius: 0.625 inches First Recess Inside Height: 8.500 inches Inside Corner Radius: 4.000 inches Body Thickness: 0.500 inches					
2.000 inches Distance From First Hole Centerline To End Along Width: 0.562 inches Inverted Radius: 0.500 inches Ear Radius: 0.625 inches First Recess Inside Height: 8.500 inches Inside Corner Radius: 4.000 inches Body Thickness: 0.500 inches Securing Device Type:					
2.000 inches Distance From First Hole Centerline To End Along Width: 0.562 inches Inverted Radius: 0.500 inches Ear Radius: 0.625 inches First Recess Inside Height: 8.500 inches Inside Corner Radius: 4.000 inches Body Thickness: 0.500 inches Securing Device Type: Threaded fastener					

Material:

Aluminum

NSN 5340-01-171-4947

Access Cover - Page 2 of 2



-			
٠.	hΔ	Iŧ.	ife:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531c0