

View Online at <https://aerobasegroup.com/nsn/5340-01-172-0066>

Hole Diameter:

Between 0.184 inches and 0.190 inches

Edge Shape:

Round, three ears and holes

First Recess Inside Height:

Between 0.280 inches and 0.290 inches

Mounting Opening Shape Style:

Open horizontal slot

End Application:

F110, ge 100 engine

Special Features:

Contains 1 hole tap drilled 0.190 in. Min to 0.195 in. Maximum dia, 0.215 in. Min to 0.220 in. Diameter counterbore, 0.060 in. Min to 0.070 in. Maximum deep, 80.0 degrees min to 100.0 degrees maximum by 0.205 in. Min to 0.220 in. Maximum csk, 0.216-28 unf-3b per mil-s-7742 threads, 2 holes tap drilled 0.271 in. Min to 0.276 in. Maximum dia, 0.500 in. Maximum depth, 80.0 degrees min to 100.0 degrees maximum by 0.323 in. Min to 0.333 in. Maximum diameter csk, 0.3125-18 unc-2b per mil-s-7742 0.370 in. Deep

Material:

Aluminum alloy

Material Specification:

Ams 4215 assn standard single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531c0