NSN 5340-01-173-3319

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-173-3319

| Mounting Hole Type: |
|--|
| Plain |
| First Leg Length: |
| 0.500 inches |
| Second Leg Length: |
| 0.500 inches |
| First Leg Hole Diameter: |
| 0.171 inches |
| First Leg Thickness: |
| 0.062 inches |
| Second Leg Thickness: |
| 0.062 inches |
| Center Section Height: |
| 7.531 inches |
| Center Section Width: |
| 1.000 inches |
| Center Section Thickness: |
| 0.062 inches |
| First Leg Width: |
| 1.000 inches |
| First Leg Distance Between Hole Centers Along Width: |
| 0.500 inches |
| First Leg Distance From Edge To Hole Center Along Width: |
| 0.250 inches |
| First Leg Distance From Edge To Hole Center Along Length: |
| 0.250 inches |
| First Leg Style: |
| Square |
| First Leg Hole Arrangement Style: |
| Two holes |
| Second Leg Relationship To First Leg: |
| Identical |
| First Leg Angle: |
| 90.0 degrees |
| Second Leg Angle: |
| 90.0 degrees |
| Special Features: |
| X0.500 in. Hole diameter two places, one hole has two flats 180.0 degrees apart center section; 2.281 in. Distance from edge to first hole |
| center along center section; 3.000 in. Distance between hole centers along center section; h32 hardness |
| Material: |

Anodize

Aluminum alloy 5052 **Surface Treatment:**

NSN 5340-01-173-3319

Double Angle Bracket - Page 2 of 2



| Sty | عا | D | 20 | 'n | n | at | ۸r | •• |
|------|----|----|----|----|----|----|----|----|
| Oty: | Œ | יש | 53 | ıy | •• | aι | vi | • |

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0