

View Online at <https://aerobasegroup.com/nsn/5340-01-174-8283>

Mounting Hole Type:

Plain

First Leg Length:

0.750 inches

Second Leg Length:

1.000 inches

Second Leg Width:

0.600 inches

First Leg Hole Diameter:

Between 0.279 inches and 0.291 inches

Second Leg Hole Diameter:

Between 0.218 inches and 0.229 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.300 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.300 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

0.600 inches

First Leg Distance From Edge To Hole Center Along Width:

0.300 inches

First Leg Distance From Edge To Hole Center Along Length:

0.300 inches

First Leg End Radius:

0.300 inches

Second Leg End Radius:

0.300 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 301 or steel comp 302

Material Specification:

Mil-s-5059 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Bac 5021, method 4, fscm 82918 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-s-5059 spec.