

View Online at <https://aerobasegroup.com/nsn/5340-01-175-7655>

Mounting Hole Type:

Countersunk and threaded

First Leg Length:

0.680 inches

Second Leg Length:

0.700 inches

Second Leg Width:

0.250 inches

First Leg Hole Diameter:

0.112 inches

Second Leg Hole Diameter:

Between 0.143 inches and 0.149 inches

Second Leg Distance Between Hole Centers Along Length:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.125 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.125 inches

First Leg Thickness:

0.150 inches

Second Leg Thickness:

0.100 inches

First Leg Width:

0.250 inches

First Leg Distance Between Hole Centers Along Length:

0.330 inches

First Leg Distance From Edge To Hole Center Along Width:

0.125 inches

First Leg Distance From Edge To Hole Center Along Length:

0.180 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

First leg extended 0.375 in. Beyond plane of second leg and has one 0.112-40 unc 2b threaded hole; second leg has two 0.050 in. By 45.0 degrees chamfered corners

Material:

Steel comp 630

Material Specification:

Ams 5643, cond a assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0