

View Online at <https://aerobasegroup.com/nsn/5340-01-175-7655>

**Mounting Hole Type:**

Countersunk and threaded

**First Leg Length:**

0.680 inches

**Second Leg Length:**

0.700 inches

**Second Leg Width:**

0.250 inches

**First Leg Hole Diameter:**

0.112 inches

**Second Leg Hole Diameter:**

Between 0.143 inches and 0.149 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.125 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.125 inches

**First Leg Thickness:**

0.150 inches

**Second Leg Thickness:**

0.100 inches

**First Leg Width:**

0.250 inches

**First Leg Distance Between Hole Centers Along Length:**

0.330 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.125 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.180 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

First leg extended 0.375 in. Beyond plane of second leg and has one 0.112-40 unc 2b threaded hole; second leg has two 0.050 in. By 45.0 degrees chamfered corners

**Material:**

Steel comp 630

**Material Specification:**

Ams 5643, cond a assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0