

View Online at <https://aerobasegroup.com/nsn/5340-01-175-9308>

Mounting Hole Type:

Plain

First Leg Length:

Between 9.0 millimeters and 10.0 millimeters

Second Leg Length:

Between 26.0 millimeters and 27.0 millimeters

Second Leg Width:

Between 9.0 millimeters and 10.0 millimeters

Second Leg Corner Radius:

Between 0.2 millimeters and 0.5 millimeters

Second Leg Hole Diameter:

Between 5.2 millimeters and 5.5 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

Between 4.0 millimeters and 5.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

6.3 millimeters

First Leg Thickness:

Between 0.5 millimeters and 0.6 millimeters

Second Leg Thickness:

Between 0.5 millimeters and 0.6 millimeters

First Leg Width:

Between 9.0 millimeters and 10.0 millimeters

First Leg Corner Radius:

Between 0.2 millimeters and 0.5 millimeters

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Color black

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t6 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 3, cl 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.