

View Online at <https://aerobasegroup.com/nsn/5340-01-176-5061>

Thread Class:

3a left internal (includes through thread)

Thread Direction:

Right-hand right external

Flange Thickness:

0.500 inches

Length:

0.875 inches

Flange Width Across Flats:

0.375 inches

Thread Qty Per Inch (tpi):

32 right external

Thread Size:

0.190 inches right external

Material:

Steel comp 1008 standoff or steel comp 1010 standoff or steel comp 1015 standoff or steel comp 1016 standoff or steel comp 1017 standoff or steel comp 1018 standoff or steel comp 1019 standoff or steel comp 1020 standoff or steel comp 1021 standoff or steel comp 1022 standoff or steel comp 1025 standoff or steel comp 1030 standoff or steel comp 1035 standoff or steel comp 1040 standoff or steel comp 1045 standoff or steel comp 1050 standoff or steel comp 1095 standoff or steel comp 1115 standoff or steel comp 1213 standoff or steel comp 1117 standoff or steel comp 1118 standoff or steel comp 1137 standoff or steel comp 1141 standoff or steel comp 1144 standoff or steel comp 1151 standoff or steel comp 1211 standoff or steel comp 1212 standoff or steel comp 1215 standoff or steel comp 1548 standoff or steel comp 1214 standoff

Material Specification:

Astm a108 assn standard all material responses standoff

Surface Treatment:

Cadmium standoff and chromate standoff

Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response standoff

Style Designator:

Flanged with left internal thread

Thread Series Designator:

Unf right external

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A08900