NSN 5340-01-178-2868

Retaining Strap - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-178-2868

Between 0.060 inches and 0.066 inches Distance Between Mounting Hole Centers: 2.600 inches Cushion: Not included Mounting Pad: Not included Mounting Hole Size: Between 0.271 inches and 0.278 inches Distance Between Base And Inside Of Arch: Between 1.354 inches and 1.360 inches Special Features: Center section contains 2 slots, 0.210 in. Min to 0.230 in. Maximum slot width, also contains an extra leg strap on one end Material:
2.600 inches Cushion: Not included Mounting Pad: Not included Mounting Hole Size: Between 0.271 inches and 0.278 inches Distance Between Base And Inside Of Arch: Between 1.354 inches and 1.360 inches Special Features: Center section contains 2 slots, 0.210 in. Min to 0.230 in. Maximum slot width, also contains an extra leg strap on one end
Cushion: Not included Mounting Pad: Not included Mounting Hole Size: Between 0.271 inches and 0.278 inches Distance Between Base And Inside Of Arch: Between 1.354 inches and 1.360 inches Special Features: Center section contains 2 slots, 0.210 in. Min to 0.230 in. Maximum slot width, also contains an extra leg strap on one end
Mounting Pad: Not included Mounting Hole Size: Between 0.271 inches and 0.278 inches Distance Between Base And Inside Of Arch: Between 1.354 inches and 1.360 inches Special Features: Center section contains 2 slots, 0.210 in. Min to 0.230 in. Maximum slot width, also contains an extra leg strap on one end
Mounting Pad: Not included Mounting Hole Size: Between 0.271 inches and 0.278 inches Distance Between Base And Inside Of Arch: Between 1.354 inches and 1.360 inches Special Features: Center section contains 2 slots, 0.210 in. Min to 0.230 in. Maximum slot width, also contains an extra leg strap on one end
Not included Mounting Hole Size: Between 0.271 inches and 0.278 inches Distance Between Base And Inside Of Arch: Between 1.354 inches and 1.360 inches Special Features: Center section contains 2 slots, 0.210 in. Min to 0.230 in. Maximum slot width, also contains an extra leg strap on one end
Mounting Hole Size: Between 0.271 inches and 0.278 inches Distance Between Base And Inside Of Arch: Between 1.354 inches and 1.360 inches Special Features: Center section contains 2 slots, 0.210 in. Min to 0.230 in. Maximum slot width, also contains an extra leg strap on one end
Between 0.271 inches and 0.278 inches Distance Between Base And Inside Of Arch: Between 1.354 inches and 1.360 inches Special Features: Center section contains 2 slots, 0.210 in. Min to 0.230 in. Maximum slot width, also contains an extra leg strap on one end
Distance Between Base And Inside Of Arch: Between 1.354 inches and 1.360 inches Special Features: Center section contains 2 slots, 0.210 in. Min to 0.230 in. Maximum slot width, also contains an extra leg strap on one end
Between 1.354 inches and 1.360 inches Special Features: Center section contains 2 slots, 0.210 in. Min to 0.230 in. Maximum slot width, also contains an extra leg strap on one end
Special Features: Center section contains 2 slots, 0.210 in. Min to 0.230 in. Maximum slot width, also contains an extra leg strap on one end
Center section contains 2 slots, 0.210 in. Min to 0.230 in. Maximum slot width, also contains an extra leg strap on one end
Material:
Nickel alloy, ams 5599
Material:
Nickel alloy 625
Style Designator:
Straight arch
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T372-a