

View Online at <https://aerobasegroup.com/nsn/5340-01-180-2287>

Mounting Hole Type:

Plain

First Leg Length:

0.656 inches

Second Leg Length:

1.781 inches

Second Leg Width:

1.000 inches

Second Leg Corner Radius:

0.250 inches

First Leg Hole Diameter:

Between 0.190 inches and 0.196 inches

Second Leg Hole Diameter:

0.196 inches

Second Leg Distance Between Lower Hole Centers Along Width:

0.469 inches

Second Leg Distance Between Hole Centers Along Length:

0.906 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.234 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.064 inches

Second Leg Thickness:

0.064 inches

First Leg Width:

1.000 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Two other holes second leg with 0.127 in. Min, 0.133 in. Maximum dia

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/4 federal specification single material response

Surface Treatment:

Primer epoxy

Surface Treatment Specification:

76 and 161 fscm 26512 mfr ref single treatment response

Style Designator:

Angle

Specification Data:

26512-gb11a1-2 manufacturers specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0