

View Online at <https://aerobasegroup.com/nsn/5340-01-181-5759>

Mounting Hole Type:

Plain

First Leg Length:

1.680 inches

Second Leg Length:

3.940 inches

Second Leg Width:

3.250 inches

First Leg Slot Length:

0.750 inches

First Leg Slot Width:

0.310 inches

Second Leg Hole Diameter:

Between 0.230 inches and 0.270 inches

Second Leg Distance Between Upper Hole Centers Along Width:

2.500 inches

Second Leg Distance Between Hole Centers Along Length:

Between 2.060 inches and 2.180 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

1.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.370 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.810 inches

First Leg Thickness:

0.188 inches

Second Leg Thickness:

0.188 inches

First Leg Width:

3.250 inches

First Leg Distance Between Hole Centers Along Width:

2.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.370 inches

First Leg Distance From Edge To Hole Center Along Length:

0.630 inches

Second Leg End Radius:

0.810 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

113.0 degrees

Special Features:

One hole second leg has diameter 0.940 in.; color forest green

Material:

Aluminum alloy 5083 or aluminum alloy 5086 or aluminum alloy 5456 or aluminum alloy 6061

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.