

View Online at <https://aerobasegroup.com/nsn/5340-01-181-5759>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.680 inches

**Second Leg Length:**

3.940 inches

**Second Leg Width:**

3.250 inches

**First Leg Slot Length:**

0.750 inches

**First Leg Slot Width:**

0.310 inches

**Second Leg Hole Diameter:**

Between 0.230 inches and 0.270 inches

**Second Leg Distance Between Upper Hole Centers Along Width:**

2.500 inches

**Second Leg Distance Between Hole Centers Along Length:**

Between 2.060 inches and 2.180 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

1.250 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.370 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.810 inches

**First Leg Thickness:**

0.188 inches

**Second Leg Thickness:**

0.188 inches

**First Leg Width:**

3.250 inches

**First Leg Distance Between Hole Centers Along Width:**

2.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.370 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.630 inches

**Second Leg End Radius:**

0.810 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

113.0 degrees

**Special Features:**

One hole second leg has diameter 0.940 in.; color forest green

**Material:**

Aluminum alloy 5083 or aluminum alloy 5086 or aluminum alloy 5456 or aluminum alloy 6061

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.