

View Online at <https://aerobasegroup.com/nsn/5340-01-181-6353>

Mounting Hole Type:

Countersunk and plain

First Leg Length:

1.010 inches

Second Leg Length:

1.140 inches

Reinforcement Method (non-core):

Gusset both legs

Second Leg Width:

2.020 inches

First Leg Hole Diameter:

Between 0.115 inches and 0.120 inches

Second Leg Hole Diameter:

Between 0.137 inches and 0.143 inches

Second Leg Distance Between Hole Centers Along Length:

0.437 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.676 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.233 inches

First Leg Thickness:

0.062 inches

Second Leg Thickness:

0.062 inches

First Leg Width:

2.020 inches

First Leg Distance Between Hole Centers Along Width:

1.795 inches

First Leg Distance Between Hole Centers Along Length:

0.515 inches

First Leg Distance From Edge To Hole Center Along Width:

0.270 inches

First Leg Distance From Edge To Hole Center Along Length:

0.185 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Cutout Length:

0.950 inches

First Leg Cutout Width:

1.480 inches

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.