

View Online at <https://aerobasegroup.com/nsn/5340-01-182-9572>

Mounting Hole Type:

Plain

First Leg Length:

0.750 inches

Second Leg Length:

1.250 inches

Second Leg Width:

5.840 inches

Second Leg Distance Between Hole Centers Along Width:

0.844 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.710 inches

Second Leg Slot Length:

0.700 inches

Second Leg Slot Width:

0.334 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

5.850 inches

First Leg End Radius:

0.250 inches

Second Leg End Radius:

0.250 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Heat treat to rc36.0-40.0 per hp1-1; 2 slots, 0.700 in. Lg., 0.334 in. W., 0.844 in. Center to center, centered 0.710 in. Along lg. And 0.500 in. Alongw.

Material:

Steel comp 4130

Material Specification:

Mil-s-18729, cond. A military specification single material response

Surface Treatment:

Phosphate manganese

Surface Treatment Specification:

H+4-7a, class (no. 30, epb4-230) assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-18729 spec.