## NSN 5340-01-184-2044

Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-184-2044

**Thread Class:** 

3b left internal (includes through thread)

**Thread Direction:** 

Right-hand right external

Thread Length:

0.5000 inches right external

**Shoulder Width Across Flats:** 

Between 0.304 inches and 0.316 inches

**Shoulder Length:** 

Between 0.115 inches and 0.135 inches

**Second Shoulder Diameter:** 

Between 0.337 inches and 0.357 inches

**Second Shoulder Length:** 

Between 0.070 inches and 0.090 inches

Length:

Between 1.470 inches and 1.530 inches

**Cross-sectional Shape:** 

Hexagon

Width Across Flats:

Between 0.3040 inches and 0.3160 inches

Thready Qty Per Inch (tpi):

32 right external

**Thread Size:** 

0.164 inches right external

Material:

Steel comp 4130 standoff or steel comp 4140 standoff or steel comp 8740 standoff or steel comp 8630 standoff

**Surface Treatment:** 

Cadmium standoff and chromate standoff

**Surface Treatment Specification:** 

Qq-p-416, ty2, cl2 federal specification single treatment response standoff

**Style Designator:** 

Two shoulders left internal and right external threads

**Thread Series Designator:** 

Unjef right external

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A08900