## NSN 5340-01-184-3830

Access Cover - Page 1 of 2

Fiig: A531c0



View Online at https://aerobasegroup.com/nsn/5340-01-184-3830

| view Offilite at https://defobasegroup.com/hist//5546-61-164-5656  |
|--|
| Cross Sectional Shape:   |
| Flat   |
| Hole Diameter:   |
| 0.218 inches   |
| Width:   |
| 5.000 inches   |
| Edge Shape:  |
| Rectangle, multi holes   |
| Length:  |
| 76.000 inches  |
| Hole Quantity Along Length:  |
| 2  |
| Hole Quantity Along Width:   |
| 4  |
| Distance Between Holes Along Length:   |
| 9.000 inches and 12.000 inches   |
| Distance Between Holes Along Width:  |
| 3.750 inches   |
| Distance From First Hole Centerline To End Along Length:   |
| 2.500 inches   |
| Distance From First Hole Centerline To End Along Width:  |
| 0.625 inches   |
| Body Thickness:  |
| 1.500 inches   |
| Securing Device Type:  |
| Threaded fastener  |
| Mounting Opening Shape Style:  |
| Unthreaded hole  |
| Special Features:  |
| Nine holes 0.166 in. Dia, four hole at top along I, 0.625 in. Distance from edge along I to centerline of holes, 4.000 in. Distance from edge      |
| along w to centerline of first hole, five holes at bottom along I, 0.625 in. Distance from edge along I to centerline of holes, 1.000 in. Distance |
| from edge along w to centerline of first hole, 6.000 in. Distance between centerline of holes along I  |
| Material:  |
| Copper   |
| Material Specification:  |
| Mil-c-15726, alloy 7030 military specification single material response  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |

## NSN 5340-01-184-3830

Access Cover - Page 2 of 2



Mil-std (military Standard):

Mil-c-15726 spec.