

View Online at <https://aerobasegroup.com/nsn/5340-01-184-7652>

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.123 inches

**Second Leg Length:**

2.313 inches

**Second Leg Width:**

3.000 inches

**First Leg Hole Diameter:**

0.410 inches

**Second Leg Hole Diameter:**

0.280 inches

**Second Leg Distance Between Upper Hole Centers Along Width:**

2.250 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.380 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

1.130 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.380 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.430 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

3.000 inches

**First Leg End Width:**

1.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

First leg has 0.750 in. W by 1.620 in. Lg notch, tapered with 0.120 in. Radius corner on each side

**Material:**

Steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020

**Surface Treatment:**

Enamel semigloss

**Surface Treatment Specification:**

Tt-e-529 federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0