

View Online at <https://aerobasegroup.com/nsn/5340-01-185-2878>

First Leg Length:

0.069 inches

Second Leg Length:

1.000 inches

End Application:

Modulator rf mid, an/alq 184

Second Leg Width:

2.060 inches

Second Leg End Width:

0.970 inches

First Leg Hole Diameter:

Between 0.143 inches and 0.149 inches

Second Leg Hole Diameter:

Between 0.405 inches and 0.412 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.660 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.700 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

2.000 inches

First Leg End Width:

1.760 inches

First Leg Distance Between Hole Centers Along Width:

1.700 inches

First Leg Distance From Edge To Hole Center Along Width:

0.150 inches

First Leg Distance From Edge To Hole Center Along Length:

0.390 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Two holes

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

2nd leg has tab with 90 degrees angle creating 3rd leg 0.550 in. By 0.750 in. W 1 hole 0.165-0.171 in. Dia

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 cl3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.