

View Online at <https://aerobasegroup.com/nsn/5340-01-185-2878>

**First Leg Length:**

0.069 inches

**Second Leg Length:**

1.000 inches

**End Application:**

Modulator rf mid, an/alq 184

**Second Leg Width:**

2.060 inches

**Second Leg End Width:**

0.970 inches

**First Leg Hole Diameter:**

Between 0.143 inches and 0.149 inches

**Second Leg Hole Diameter:**

Between 0.405 inches and 0.412 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.660 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.700 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

2.000 inches

**First Leg End Width:**

1.760 inches

**First Leg Distance Between Hole Centers Along Width:**

1.700 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.150 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.390 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

2nd leg has tab with 90 degrees angle creating 3rd leg 0.550 in. By 0.750 in. W 1 hole 0.165-0.171 in. Dia

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8 h32 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 cl3 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.