

View Online at <https://aerobasegroup.com/nsn/5340-01-186-3506>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.594 inches

**Second Leg Length:**

0.750 inches

**Second Leg Width:**

1.187 inches

**First Leg Hole Diameter:**

Between 0.097 inches and 0.100 inches

**Second Leg Hole Diameter:**

Between 0.192 inches and 0.196 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.312 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.312 inches

**First Leg Thickness:**

0.040 inches

**Second Leg Thickness:**

0.040 inches

**First Leg Width:**

0.875 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

0.375 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**Second Leg End Radius:**

0.312 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

First and second legs are tapered; for right hand use

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5, t42 federal specification single material response

**Surface Treatment:**

Plastic epoxy

**Surface Treatment Specification:**

Mil-p-23377 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-p-23377 spec.