

View Online at <https://aerobasegroup.com/nsn/5340-01-186-4028>

Center To Center Distance Between Bolt Holes Along Width:

Between 3.355 inches and 3.395 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 5.230 inches and 5.270 inches

Wheel Quantity:

1

Safe Operating Load Rating:

1200.0 pounds

Material And Location:

Steel plate err-100 err-100 or iron, cast plate err-100 err-100 or iron, malleable plate err-100 err-100 or aluminum alloy plate err-100 err-100 or magnesium alloy plate err-100 err-100

Surface Treatment And Location:

Paint body

Wheel Type:

Built up

Wheel Diameter:

8.000 inches

Effective Height:

Between 10.156 inches and 10.344 inches

Features Provided:

Swivel lock and swivel lubrication fitting

Plate Style:

Rectangular

Wheel Bearing Type:

Ball or roller

Swivel Bearing Type:

Ball or roller

Swivel Bearing Arrangement:

Two row

Tread Width:

2.500 inches

Caster Plate Length:

Between 7.188 inches and 7.312 inches

Caster Plate Width:

Between 5.313 inches and 5.437 inches

Caster Plate Mounting Hole Diameter:

Between 0.521 inches and 0.541 inches

Style Designator:

Swivel offset

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A25600