

View Online at <https://aerobasegroup.com/nsn/5340-01-186-9350>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 0.750 inches and 0.780 inches

**Second Leg Length:**

Between 1.250 inches and 1.280 inches

**Second Leg Width:**

Between 1.480 inches and 1.520 inches

**Second Leg Corner Radius:**

0.250 inches

**Second Leg Hole Diameter:**

Between 0.220 inches and 0.230 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

Between 0.490 inches and 0.530 inches

**Second Leg Distance Between Second And Third Hole Centers Along Width:**

Between 0.490 inches and 0.530 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.230 inches and 0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.230 inches and 0.300 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

Between 1.480 inches and 1.520 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

No hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5 t81 federal specification single material response

**Surface Treatment:**

Plastic epoxy

**Surface Treatment Specification:**

Mil-p-23377 w/ plastic polyamide military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-p-23377 spec.