
Angle Bracket - Page 1 of 2

Mounting Hole Type:





Plain First Leg Length: 1.700 inches Second Leg Length: 2.000 inches **Reinforcement Method (non-core):** Gusset both ends Second Leg Width: 2.240 inches First Leg Hole Diameter: 0.281 inches Second Leg Hole Diameter: 0.178 inches Second Leg Distance Between Hole Centers Along Width: 1.250 inches Second Leg Distance Between Hole Centers Along Length: 1.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.495 inches Second Leg Distance From Edge To Hole Center Along Length: 0.210 inches **First Leg Thickness:** 0.090 inches Second Leg Thickness: 0.090 inches First Leg Width: 2.240 inches First Leg Distance Between Hole Centers Along Width: 0.670 inches First Leg Distance Between Hole Centers Along Length: 0.657 inches First Leg Distance From Edge To Hole Center Along Width: 0.590 inches First Leg Distance From Edge To Hole Center Along Length: 0.530 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square

NSN 5340-01-189-7557

Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Second leg has a 1.440 in. Diameter hole: first leg is split in two parts

Material:

Aluminum alloy 6010

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0