NSN 5340-01-189-7562

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-189-7562

Mounting Hole Type:
Counterbored and countersunk and threaded
First Leg Length:
0.375 inches
Second Leg Length:
1.890 inches
Second Leg Width:
1.800 inches
Second Leg End Width:
0.180 inches
First Leg Hole Diameter:
0.138 inches
Second Leg Hole Diameter:
Between 0.127 inches and 0.133 inches
Second Leg Distance Between Upper Hole Centers Along Width:
1.502 inches
Second Leg Distance Between Hole Centers Along Length:
0.3755 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
0.3755 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.149 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.169 inches
First Leg Thickness:
0.280 inches
Second Leg Thickness:
0.070 inches
First Leg Width:
2.120 inches
First Leg Distance Between Hole Centers Along Width:
1.750 inches
First Leg Distance From Edge To Hole Center Along Width:
0.185 inches
First Leg Distance From Edge To Hole Center Along Length:
0.180 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:

Square and tapered

NSN 5340-01-189-7562

Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:
Three holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Special Features:
First leg has a 0.305 in. Deep by 1.370 in. Lg opening; second leg has a 1.250 in. Diameter hole; item supplied with two washer, flats, two
washer, lock and two screws
Material:
Steel comp 303se
Material Specification:
Ams 5738 assn standard single material response
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924, cl 4 military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Filg:
A042a0
Mil-std (military Standard):
Mil-c-13924 spec.