

View Online at <https://aerobasegroup.com/nsn/5340-01-189-7562>

Mounting Hole Type:

Counterbored and countersunk and threaded

First Leg Length:

0.375 inches

Second Leg Length:

1.890 inches

Second Leg Width:

1.800 inches

Second Leg End Width:

0.180 inches

First Leg Hole Diameter:

0.138 inches

Second Leg Hole Diameter:

Between 0.127 inches and 0.133 inches

Second Leg Distance Between Upper Hole Centers Along Width:

1.502 inches

Second Leg Distance Between Hole Centers Along Length:

0.3755 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.3755 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.149 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.169 inches

First Leg Thickness:

0.280 inches

Second Leg Thickness:

0.070 inches

First Leg Width:

2.120 inches

First Leg Distance Between Hole Centers Along Width:

1.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.185 inches

First Leg Distance From Edge To Hole Center Along Length:

0.180 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

First leg has a 0.305 in. Deep by 1.370 in. Lg opening; second leg has a 1.250 in. Diameter hole; item supplied with two washer, flats, two washer, lock and two screws

Material:

Steel comp 303se

Material Specification:

Ams 5738 assn standard single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924, cl 4 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-13924 spec.