

View Online at <https://aerobasegroup.com/nsn/5340-01-193-1931>

Mounting Hole Type:

Plain

First Leg Length:

1.500 inches

Second Leg Length:

1.500 inches

End Application:

An/usm-464

Second Leg Width:

16.380 inches

Second Leg End Width:

16.140 inches

First Leg Hole Diameter:

Between 0.312 inches and 0.315 inches

Second Leg Hole Diameter:

Between 0.265 inches and 0.268 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

5.000 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.120 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

16.380 inches

First Leg End Width:

16.140 inches

First Leg Distance Between First And Second Hole Centers Along Width:

7.000 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

7.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.620 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6063

Material Specification:

Qq-a-200/9, temper-t52 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cla 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.