NSN 5340-01-193-1931

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-193-1931

Mounting Hole Type:
Plain
First Leg Length:
1.500 inches
Second Leg Length:
1.500 inches
End Application:
An/usm-464
Second Leg Width:
16.380 inches
Second Leg End Width:
16.140 inches
First Leg Hole Diameter:
Between 0.312 inches and 0.315 inches
Second Leg Hole Diameter:
Between 0.265 inches and 0.268 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
5.000 inches
Second Leg Distance Between Second And Third Hole Centers Along Width:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Width:
1.120 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.750 inches
First Leg Thickness:
0.125 inches
Second Leg Thickness:
0.125 inches
First Leg Width:
16.380 inches
First Leg End Width:
16.140 inches
First Leg Distance Between First And Second Hole Centers Along Width:
7.000 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
7.000 inches
First Leg Distance From Edge To Hole Center Along Width:
0.500 inches
First Leg Distance From Edge To Hole Center Along Length:
0.620 inches
First Leg Style:
Chamfered ends

NSN 5340-01-193-1931 Angle Bracket - Page 2 of 2



First Leg Hole Arrangement Style:
Three holes
Second Leg Style:
Chamfered ends
Second Leg Hole Arrangement Style:
Three holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Material:
Aluminum alloy 6063
Material Specification:
Qq-a-200/9, temper-t52 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541, cla 1a military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.