

View Online at <https://aerobasegroup.com/nsn/5340-01-193-2469>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 0.730 inches and 0.770 inches

**Second Leg Length:**

Between 0.740 inches and 0.760 inches

**Second Leg Width:**

Between 0.980 inches and 1.020 inches

**Second Leg Corner Radius:**

0.250 inches

**First Leg Hole Diameter:**

Between 0.129 inches and 0.134 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.497 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**Second Leg Slot Length:**

0.499 inches

**Second Leg Slot Width:**

Between 0.224 inches and 0.229 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

Between 0.980 inches and 1.020 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 0.490 inches and 0.510 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5 t81 federal specification single material response

**Surface Treatment:**

Primer

**Surface Treatment Specification:**

Mms425 fscm 76301 mfr ref single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0