
Angle Bracket - Page 1 of 2





Mounting Hole Type:

Plain

First Leg Length:

1.750 inches

Second Leg Length:

3.250 inches

Second Leg Width:

2.000 inches

First Leg Hole Diameter:

0.620 inches

Second Leg Hole Diameter:

0.440 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.680 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

2.000 inches

First Leg Distance Between Hole Centers Along Width:

1.060 inches

First Leg Distance From Edge To Hole Center Along Width:

0.470 inches

First Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Radius 0.180 in. Bend 2.760 in. Min, 3.000 in. Maximum Ig second leg; color white number 17875

NSN 5340-01-195-5913

Angle Bracket - Page 2 of 2



Material:

Steel

Material Specification:

Astm a36 assn standard single material response

Surface Treatment:

Plastic polyamide

Surface Treatment Specification:

Mil-c-22750 type 1 cl optional military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-22750 spec.