

View Online at <https://aerobasegroup.com/nsn/5340-01-197-2418>

Mounting Hole Type:

Plain

First Leg Length:

1.000 inches

Second Leg Length:

2.250 inches

Second Leg Width:

9.000 inches

First Leg Hole Diameter:

0.160 inches

Second Leg Hole Diameter:

0.160 inches

Second Leg Distance Between Hole Centers Along Width:

7.760 inches

Second Leg Distance Between Hole Centers Along Length:

1.250 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

1.940 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

1.940 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.620 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.620 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

9.000 inches

First Leg Distance Between Hole Centers Along Width:

7.880 inches

First Leg Distance Between First And Second Hole Centers Along Width:

2.000 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

2.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Style:

Square

Second Leg Style:

Square

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

First leg has five holes; second leg has ten holes; hole spacing designed for right hand use

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/8, t6 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.