NSN 5340-01-197-2418

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-197-2418

Mounting Hole Type:
Plain
First Leg Length:
1.000 inches
Second Leg Length:
2.250 inches
Second Leg Width:
9.000 inches
First Leg Hole Diameter:
0.160 inches
Second Leg Hole Diameter:
0.160 inches
Second Leg Distance Between Hole Centers Along Width:
7.760 inches
Second Leg Distance Between Hole Centers Along Length:
1.250 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
1.940 inches
Second Leg Distance Between Second And Third Hole Centers Along Width:
1.940 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.620 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.620 inches
First Leg Thickness:
0.125 inches
Second Leg Thickness:
0.125 inches
First Leg Width:
9.000 inches
First Leg Distance Between Hole Centers Along Width:
7.880 inches
First Leg Distance Between First And Second Hole Centers Along Width:
2.000 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
2.000 inches
First Leg Distance From Edge To Hole Center Along Width:
0.500 inches
First Leg Distance From Edge To Hole Center Along Length:
0.380 inches
First Leg Style:
Square

NSN 5340-01-197-2418 Angle Bracket - Page 2 of 2



Second Leg Style:
Square
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Special Features:
First leg has five holes; second leg has ten holes; hole spacing designed for right hand use
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-200/8, t6 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541, cl 1a military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.