

View Online at <https://aerobasegroup.com/nsn/5340-01-197-8214>

Mounting Hole Type:

Plain

First Leg Length:

Between 1.720 inches and 1.780 inches

Second Leg Length:

Between 4.220 inches and 4.280 inches

Second Leg Width:

Between 0.970 inches and 1.030 inches

First Leg Hole Diameter:

Between 0.521 inches and 0.541 inches

Second Leg Hole Diameter:

Between 0.396 inches and 0.416 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.470 inches and 0.530 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.470 inches and 0.530 inches

First Leg Thickness:

0.1345 inches

Second Leg Thickness:

0.1345 inches

First Leg Width:

Between 0.970 inches and 1.030 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.470 inches and 0.530 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.470 inches and 0.530 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 89.0 degrees and 91.0 degrees

Material:

Steel comp 1009 or steel comp 1137

Material Specification:

Astm a569 assn standard 1st material response or astm a109 assn standard 2nd material response

Surface Treatment:

Primer

Surface Treatment Specification:

Tt-p-636 federal specification single treatment response or tt-p-664 federal specification single treatment response or mil-p-52995 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-p-52995 spec.