

View Online at <https://aerobasegroup.com/nsn/5340-01-197-8215>

Mounting Hole Type:

Plain

First Leg Length:

6.430 inches

Second Leg Length:

8.930 inches

Second Leg Width:

7.250 inches

First Leg Slot Length:

0.810 inches

First Leg Slot Width:

0.406 inches

Second Leg Hole Diameter:

0.406 inches

Second Leg Distance Between Lower Hole Centers Along Width:

3.000 inches

Second Leg Distance Between Hole Centers Along Length:

2.300 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

1.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.590 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.780 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.230 inches

First Leg Width:

7.250 inches

First Leg Distance Between Hole Centers Along Width:

3.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.590 inches

First Leg Distance From Edge To Hole Center Along Length:

0.680 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Second leg has two 0.469 in. Diameter holes and two spacers welded over two holes

Material:

Steel or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1144

Material Specification:

Astm a283 assn standard 1st material response or astm a36 assn standard 2nd material response or astm a36 assn standard 3rd material response or astm a36 assn standard 4th material response or astm a36 assn standard 5th material response

Surface Treatment:

Enamel or enamel lusterless

Surface Treatment Specification:

Mil-e-52798 military specification 1st treatment response or mil-e-52835 military specification 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-e-52798 spec.